

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Your petitioner, Andrew J. CLEVELAND, a citizen of the
United States and a resident of Reno, Nevada, and whose post
5 office address is 5419 Greenview Court, Reno, NV 89502, prays
that letters patent may be granted to him for a

POWER CONTROLLER WITH DC ARC-SUPPRESSION RELAYS

10 set forth in the following specification.

002701 45163950

POWER CONTROLLER WITH DC ARC-SUPPRESSION RELAYS

BACKGROUND OF THE INVENTION

5

Field of the Invention

The invention relates generally to computer network power controllers and more particularly to high-amperage 48-volt DC circuit relay arc-suppression.

10

Description of the Prior Art

There is a growing need for competitive local exchange carriers to manage remote power control functions of internetworking devices at telephone company (telco) central offices. Competitive local exchange carriers (CLECs), incumbent local exchange carriers (ILECs), independent telephone companies, and other next generation service providers are now all offering a digital subscriber line (DSL) service that promises high-speed Internet access for both homes and businesses. DSL is expected to replace integrated services digital network (ISDN) equipment and lines, and DSL competes very well with the T1 line that has historically been provided by ILECs. A DSL drop costs about \$40-60 per month, and is expected to quickly become the dominant subscriber-line technology.

The DSL service is provided by a switch that is co-located in a telco central office, i.e., a digital subscriber line access multiplexer (DSLAM). Many new competitive local exchange carriers are now deploying DSL service in several states. They are installing digital subscriber line access multiplexers in many locations. Such digital subscriber line

00220157-101200

access multiplexers are now available from a number of different manufacturers, e.g., Paradyne, Copper Mountain, Ascend, etc.

Nearly all such digital subscriber line access
5 multiplexers are powered by 48-VDC battery power and all have
operator console ports. And for emergencies, these DSLAMs
usually have two independent 48-VDC battery power supplies,
e.g., an A-channel and a B-channel. Most commercial DSLAMs
are also controlled by large operating systems that host
10 various application software. Unfortunately, this means most
DSLAMs have the potential to fail or lock-up, e.g., due to
some software bug.

When a digital subscriber line access multiplexer does lock-up, the time-honored method of recovering is to cycle the power, i.e., reboot. But when a digital subscriber line access multiplexer is located at a telco central office, such location practically prevents it being easy to reboot manually.

20 There are many large router and ATM switch farms around
the country that are equipped by the leading vendors, e.g.,
Cisco, Bay Networks/Nortel, Ascend, Lucent, Fore, etc. So
each of these too has the potential to lock-up and need
rebooting, and each of these is very inconvenient to staff or
visit for a manual reboot when needed.

25 Server Technology, Inc., (Sunnyvale, CA) markets a 48-
VDC remote power manager and intelligent power distribution
unit that provides for remote rebooting of remote digital
subscriber line access multiplexers and other network
equipment in telco central offices and router farms. The
30 SENTRY 48-VDC is a network management center that eliminates
the dispatching of field service technicians to cycle power

and rectify locked-up digital subscriber line access multiplexers.

Statistics show that seventy percent, or more, of all network equipment lock-ups can be overcome by rebooting, e.g., cycling power off and on. A remote power controller, like the SENTRY, can reduce network outages from hours to minutes.

In a typical installation, the telco central office provides the competitive local exchange carriers with bare rack space and a 48-VDC power feed cable that can supply 60-100 amps. The single power input is conventionally distributed through a fuse panel to several digital subscriber line access multiplexers in a RETMA-type equipment rack. Individual fuses in such fuse panel are used to protect each DSLAM from power faults.

But such fuses frequently weld themselves to their sockets in the fuse panel due to loose contacts and high amperage currents. It is ironic therefore that many digital subscriber line access multiplexers do not have power on/off switches. Thus it requires the fuse to be pried out and put back in so the DSLAM can be powered-off for rebooting. But when the fuse is welded, removing the fuse without damaging the fuse panel can be nearly impossible.

The Server Technology SENTRY 48-VDC accepts from the telco or other site host an A-power feed cable and B-power feed cable. Internally, DC-power is distributed to a set of "A" and "B" rear apron output terminal blocks that are protected by push-to-reset circuit breakers. The fuse panel is no longer required. The A-feed and B-feed are then matched to the newer digital subscriber line access multiplexers that also require A-power supply and B-power supply inputs.

0022707 " 101200

Sometimes digital signaling lines can lose the carrier. In such cases, the respective DSLAM must be rebooted to restore the DS3 line. A technician is conventionally required to visit the DSLAM, and use a console port to
5 monitor how the software reboots, and if communications are correctly restored to the DS3.

A SENTRY 48-VDC can be used to remotely power-off the digital subscriber line access multiplexer in the event the carrier is lost. A companion asynchronous communications
10 switch can be used to establish a connection to the DSLAM's console port. Power can be cycled to the DSLAM, and the asynchronous communications switch used to monitor the reboot operation to make certain that the carrier to the DS3 line is restored. The asynchronous communications switch is a low-
15 cost alternative to the expensive terminal server typically used for console port access. The reboot process and the console port monitoring process can both be managed from an operations center, without the need to dispatch technical personnel to the remote location.

The floor space that a competitive local exchange carrier's equipment rack sits upon is very expensive, so the equipment stuffed in the vertical space in a rack ("U-space") must be as compact as possible. A typical rack may house
20 several digital subscriber line access multiplexers, a terminal server, a fuse panel, and 48-VDC modems. A SENTRY 48-VDC uses "3U" (5.25 inches) of vertical RETMA-rack space, and combines the functions of a fuse panel, a terminal
25 server, and a modem. As many as eight 20-amp devices, or four 35-amp devices can be supported.

Power controllers, like the Server Technology SENTRY, use electromechanical relays to open and close the 48-volt supply lines to the network equipment. Unfortunately, the
30

00689157-101200

same physical phenomena that welds the fuses in their holders can also weld or destroy the contacts of these relays.

Most electric welders generate the high heats necessary to fuse metal together by arcing a direct current (DC) low voltage (under 50-volts) and high current (over 50-amps) across an electrode gap. Such conditions occur in a power controller's relay, especially when the relay contacts are opening. The mass inertia of the contact mechanism has to be overcome before the contacts can open. The contacts accelerate apart, but are moving only very slowly at the start. Electric arcs, once generated, will continue even though the electrode separation distance is increased. This is the so-called Jacob's Ladder effect. The ionized air and the heated contacts increase the distance an arc can bridge. The arcing stops only after the contacts are very wide apart.

In contrast, a pair of open relay contacts will not arc until the contacts get very close to one another. By this time, the contact closure is moving at its near maximum velocity. So the remaining gap that needs to be closed up when the arc commences will vanish quickly.

SUMMARY OF THE PRESENT INVENTION

It is therefore an object of the present invention to provide a DC arc-suppressor for network appliance power managers.

It is another object of the present invention to provide a power controller with long-lasting and reliable relay operation.

Briefly, a DC arc-suppressor embodiment of the present invention for network appliance power managers comprises an

electromechanical relay that controls the flow of battery power to a network appliance by remote control. The relay includes electrical contacts that open to interrupt the flow of current in response to an off-command signal. A

5 transistor is connected in shunt across the relay contacts to temporarily divert such flow of current. A timing circuit is connected to respond to the off-command signal by first turning on the shunt transistor, then open the relay contacts, then turn off the shunt transistor. Such shunt
10 transistor is sized to carry the full rated power of the relay contacts, but only for the few milliseconds that are needed to allow the relay contacts to fully separate.

An advantage of the present invention is that a DC arc-suppressor is provided for network appliance power managers.

15 Another advantage of the present invention is that a power controller is provided for network appliances.

These and many other objects and advantages of the present invention will no doubt become obvious to those of ordinary skill in the art after having read the following
20 detailed description of the preferred embodiments which are illustrated in the various drawing figures.

25 IN THE DRAWINGS

Fig. 1 is schematic diagram of a power controller embodiment of the present invention that includes a DC arc-suppression circuit;

30 Fig. 2 is a timing diagram related to various signal points in Fig. 1; and

00689457-101200

Fig. 3 is a functional block diagram that shows a dual-source battery power manager wired to power-cycle DSLAM, routers, and other network devices.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 illustrates a power controller embodiment of the present invention, referred to herein by the general reference numeral 100. The power controller 100 connects to a computer data network 102, e.g., the Internet, and can send status and receive commands with a network client 104. A power-OFF command raises a signal line 105 and triggers a one-shot multivibrator 106. A twenty millisecond long pulse is fed to an opto-isolator 108 through a dropping resistor 110. This turns-on a power metal-oxide-semiconductor field-effect transistor (MOSFET) 111.

The raising of signal line 105 by the power-OFF command also is fed through a two-millisecond delay circuit 112 and is forwarded to another opto-isolator 114 through a dropping resistor 116. A switch transistor 115 turns-on and energizes an inductive armature 118 in an electro-mechanical relay.

A set of station batteries 120, e.g., a 48-volt bank at a Telco Central Office, are connected through a master switch 122 and a pair of normally closed relay contacts 124 to a load 126. Network routers, bridges, and other computer network equipment are examples of what is represented by load 126. A suppression diode 128 helps control transients that occur across the load during the operation of the relay contacts 124. A sense resistor 130 is useful for the monitoring of load currents with a voltmeter or oscilloscope.

0022101 25T 68960

A conventional arc-suppression network comprising a capacitor 132, a resistor 134, and a diode 136, are connected across the relay contacts 124 to help control arcing and contact burning.

5 Fig. 2 illustrates some of the critical signal timing that occurs in power controller 100 during operation. A signal-A 202 corresponds to the output of the network client 104, e.g., signal line 105. A signal-B 204 corresponds to the load output current, as seen as a voltage across sense
10 resistor 130. A signal-C 206 corresponds to the output of the one-shot multivibrator 106. A signal-D 208 corresponds to the output of the delay circuit 112 as seen by the dropping resistor 116.

During operation, at a time t_0 , the power controller 100
15 is energized. At a time t_1 , the network client 104 receives a power-OFF command, and signal-A 202 is raised. This triggers the one-shot multivibrator 106 and causes a twenty millisecond pulse output to appear as signal-C 206. Such turns-on MOSFET power transistor 111. The signal-A 202 being
20 raised also causes signal-D 208 to follow suit, but with a two millisecond delay. Such energizes relay 118 and pulls open contacts 124. The rising-edge delay of two-milliseconds is represented by the slope of signal-D between times t_1 and t_2 . Signal-B 204 automatically falls back at time t_3 . The
25 MOSFET power transistor 111 turns off, having done its job of shunting the load current while the relay contacts were breaking.

At time t_4 , the network client 104 receives a power-ON command, and signal-A 202 is lowered. This causes signal-D
30 208 to drop and the relay contacts 124 close at time t_5 . The one-shot multivibrator 106 is unaffected because it is positive-edge triggered only.

00689157-101200

The one-shot multivibrator 106 can be implemented with a National Semiconductor NE555. The opto-isolators 108 and 114 can comprise photo-relays.

Fig. 3 represents a system 300 that includes a dual 100-amp battery source power manager 302 wired to power-cycle two DSLAMs 304 and 305, four routers 306, 307, 308 and 309, and two generic network devices 310 and 311.

The chassis are all mounted in a single RETMA-rack 312. An A-channel power connector 314 and a B-channel power connector 316 on the power manager 302 receive two circuits of 48-volt DC battery power from a telco site. A pair of batteries 318 and 320 represent these sources. A plurality of power control modules 322-329 internal to the power manager 302 are independently controlled from a network connection 330 and can individually control A-channel and B-channel DC-power supplied to each DSLAM 304 and 305, routers 306, 307, 308 and 309, and generic network devices 310 and 311. Such power control modules 322-329 include the DC arc-suppression circuitry of Fig. 1.

When any of the DSLAMs 304 and 305, routers 306, 307, 308 and 309, and generic network devices 310 and 311 need to be remotely rebooted, an appropriate network data is sent to the responsible power control modules 322-329 to cause both A-channel and B-channel DC power to cycle off and on.

Although the present invention has been described in terms of the present embodiment, it is to be understood that the disclosure is not to be interpreted as limiting. Various alterations and modifications will no doubt become apparent to those skilled in the art after having read the above disclosure. Accordingly, it is intended that the appended claims be interpreted as covering all alterations and

09689457-101200

modifications as fall within the true spirit and scope of the invention.

What is claimed is:

09689157-101200